

# *Dimatec*

Energy Efficient Lighting



**Interior and Exterior LED's** Energy Saving - Reduced Maintenance - Convenient Features

# Table of Contents

---

1	<b>LED Ceiling Lights</b> Without Switch Touch-switch	15	<b>Mini Spot Lights</b>
4	<b>Swivel Reading Lights</b> Manual-switch Touch-switch	15	<b>Track Lights</b>
6	<b>Flexible Reading Lights</b> Manual-switch Touch-switch	16	<b>Cabinet Lights</b>
9	<b>Ultra-slim Spot Lights</b> Recessed	16	<b>LED Bars</b> Recessed Recessed, Touch-switch Surface-mounted Surface-mounted, Touch-switch
9	<b>Recessed Spot Lights</b> Manual-switch Touch-switch	18	<b>LED Strips and Profiles</b>
11	<b>Swivel Spot Lights</b> Recessed, Touch-switch Recessed, Manual-switch	19	<b>Garage and Portable Lights</b>
13	<b>IP-Graded Spot Lights</b> Recessed	20	<b>Awning Lights</b>
14	<b>Surface-mounted Spot Lights</b> Manual-switch Touch-switch	21	<b>External Over-door Lights</b>
		21	<b>Awning Light Track</b>
		21	<b>Custom Designed Lighting</b>

## LED Ceiling Lights Without Switch

Dimmable lights which diffuse a uniform and comfortable glow. Featuring a total thickness of 6 mm, LED ceiling lights are surface-

mounted and do not require any cut-outs to be recess into the ceiling.

Round ceiling light  
Ø 17



**200 PAN72BD-BX**

White Frame

12V - 5.5W  
Diffused Daylight  
4000 °K  
Size: Ø 168 x 6mm

**200 PAN72SD-BX**

Silver Metallic Frame

**200 PAN72CRD-BX**

Chrome Frame

Round ceiling light  
Ø 22



**200 PAN80BD-BX**

White Frame

12V - 6.5W  
Diffused Daylight  
4000 °K  
Size: Ø 217 x 6mm

**200 PAN80SD-BX**

Silver Metallic Frame

**200 PAN80CRD-BX**

Chrome Frame

Round ceiling light  
Ø 31



**200 PAN128BD-BX**

White Frame

12V - 11W  
Diffused Daylight  
4000 °K  
Size: Ø 310 x 6 mm

**200 PAN128SD-BX**

Silver Metallic Frame

**200 PAN128CRDBX**

Chrome Frame

Oval ceiling light with  
blue night light



**200 MLO6.3-1**

Mirror Finish

12V - 6.01W  
Daylight 3000 °K  
Size: 200 x 120 x  
10mm

**200 MLO6.3D1**

Daylight 4000 °K

## LED Ceiling Lights

Without Switch



### 200 PAN2010B

White Frame  
12V - 6W  
Diffused Daylight  
3000 °K  
Size: 200 x 100 x 5mm

### 200 PAN2010BDY

White Frame  
4000 °K



### 200 PAN1010BY

White Frame  
12V - 3W  
Diffused Warm White  
3000 °K  
Size: 100 x 100 x 5mm

### 200 PAN1010BD

White Frame  
4000 °K

### 200 PAN1010SDY

Silver Frame  
4000 °K


## LED Ceiling Lights

Touch Switch




### 200 MLQ3D

Mirror Finish  
12V - 3.14W  
Daylight 4000 °K  
Size: 100 x 85 x 10mm  
Blue Nightlight



### 200 MLRE6.3D

Mirror Finish  
12V - 6.15W  
Daylight 4000 °K  
Size: 195 x 85 x 10mm  
Blue Nightlight



### 200 MLRC6.3D

Mirror Finish  
12V - 6.31W  
Daylight 4000 °K  
Size: 220 x 110 x 10mm  
Blue Nightlight



### 200 TL2010DN1

Mirror Finish  
12V - 3.16W  
Daylight 4000 °K  
Size: 200 x 90 x 20mm



**200 MLO6.3D**  
Mirror Finish  
12V - 6.01W  
Daylight 4000 °K  
Size: 200 x 120 x 10mm



**200 MLR2.2D**  
Mirror Finish  
12V - 2.2W  
Daylight 4000 °K  
Size: Ø 70 x 10mm



**200 MLR3.2D**  
Mirror Finish  
12V - 3.2W  
Daylight 4000 °K  
Size: Ø 100 x 10mm



**200 MLR4.7D**  
Mirror Finish  
12V - 4.7W  
Daylight 4000 °K  
Size: Ø 130 x 10mm

Ø 17



**200 PAN72BDT-BX**  
White Frame  
12V - 5.5W  
Diffused Daylight  
4000 °K  
Size: Ø 168 x 6mm

**200 PAN72SDT-BX**  
Metallic Silver Frame

**200 PAN72CRDTBX**  
Chrome Frame

Ø 22



**200 PAN80BDT-BX**  
White Frame  
12V - 6.5W  
Diffused Daylight  
4000 °K  
Size: Ø 217 x 6mm

**200 PAN80SDT-BX**  
Metallic Silver Frame

**200 PAN80CRDTBX**  
Chrome Frame

Ø 31



**200 PAN128BDT-BX**  
White Frame  
12V - 11W  
Diffused Daylight  
4000 °K  
Size: Ø 310 x 6mm

**200 PAN128SDT-BX**  
Metallic Silver Frame

**200 PAN128CDT-BX**  
Chrome Frame

# Swivel Reading Lights

## Mechanical Switch



**200 FAA1CR**  
 Chrome  
 12V - 1W  
 Warm White 3000 °K  
 Size: Base Ø 60mm  
 Total H: 75mm

**200 FAA1CRD**  
 Chrome  
 Warm White 4000 °K

**200 FAA1CRD**  
 Chrome  
 Warm White 4000 °K



**200 FAA2AL2**  
 Brushed Aluminum  
 12V - 2W  
 Warm White 3000 °K  
 Size: Base Ø 60mm  
 Total H: 75mm

**200 FAA2CRRB**  
 Chrome  
 Warm White 4000 °K

Two power levels



**200 FAA2AL-U2**  
 Brushed Aluminum  
 12V - 2W  
 Warm White 3000 °K  
 Size: Base Ø 60mm  
 Total H: 75mm  
 USB Port 5V - 2.1A

**200 FAA2CRRB-U**  
 Chrome  
 Warm White 4000 °K

Two power levels



**200 FAA1NEC**  
 Black  
 12V - 1W  
 3000 °K  
 Size: Base Ø 50mm  
 Total H: 75mm  
 USB Port 5V - 2.1A

**200 FAA1NECD1**  
 Black  
 4000 °K



**200 FAA1NED1**  
 Black  
 12V - 1W  
 4000 °K  
 Size: Base Ø 50mm  
 Total H: 75mm



**200 FAC2N-U**  
 Black / Chrome  
 12V - 2W  
 3000 °K  
 Size: Base Ø 60mm  
 USB Port 5V - 2.1A



**200 FJC1.8ACRM**

Chrome  
12V - 1.50W  
3000 °K  
Size: Base Ø 50mm  
Total H: 80mm



**200 FCI1NS**

Nickel Brushed  
12V - 1W  
3000 °K  
Size: 220 x 110 x 10 mm

**Swivel Reading Lights**

Touch Switch

—USB



**200 FAA1CRTDU1**

Chrome  
12V - 1W  
4000 °K  
Size: Base Ø 60mm  
Total H: 75mm  
USB Port 5V - 2.1A



**200 FAA2CRDBT**

Chrome  
12V - 1W  
4000 °K  
Size: Base Ø 60mm  
Total H: 75mm



**200 SZ1NSA**

Nickel Brushed  
12V - 1.30W  
4000 °K  
Size: Base Ø 60mm  
Total H: 90mm



**200 SZ1NST**

Nickel Brushed  
12V - 1.30W  
4000 °K  
Size: Base Ø 60mm  
Total H: 90mm



**200 FAA1CRT**

Chrome  
12V - 1W  
3000 °K  
Size: Base Ø 60mm  
Total H: 75mm

**200 FAA1CRTD1**

4000 °K

# Flexible Reading Lights

## Mechanical Switch

—USB



**200 FXA1CR-U**

Chrome  
12V - 1W  
3000 °K  
Size: Base Ø 60mm  
Length: 150mm  
USB Port 5V - 2.1A

**200 FXA1CR-UX**

Size: Base Ø 50mm

**200 FXA1CRB-UX**

—USB



**200 FX1CR-U**

Chrome  
12V - 2W  
3000 °K  
Size: Base Ø 50mm  
Length: 150mm  
USB Port 5V - 2.1A

**200 FX1CRD-U**

Chrome  
4000 °K

—USB



**200 FXJC1.8UCRM**

Chrome  
12V - 1.50W  
4000 °K  
Size: Base Ø 55mm  
Length: 150mm  
USB Port 5V - 2.1A

**200 FXJC1.8UNM1**

Black  
4000 °K



**200 FXJ0.6CR**

Chrome  
12V - .67W  
3000 °K  
Size: Base Ø 55mm  
Length: 210mm

**200 FXJ0.6CRD**

Chrome  
4000 °K



**200 FXA1CR**

Chrome  
12V - 1W  
3000 °K  
Size: Base Ø 60mm  
Length: 225mm

**200 FXA1CRD**

Chrome  
4000 °K



**200 GN1S**

Silver

12V - 1.2W  
4000 °K  
Length: 400mm



**200 FXA1CRD1X**

Chrome

12V - 1W  
4000 °K  
Size: Base Ø 50mm  
Length: 300mm



**200 FXB1CR**

Chrome

12V - 1W  
3000 °K  
Size: Base Ø 60mm  
Length: 150mm



**200 FXJC1.8ACRM**

Chrome

12V - 1.55W  
3000 °K  
Size: Base Ø 55mm  
Length: 210mm



**200 FXA2CRRB**

Chrome

12V - 1W  
4000 °K  
Size: Base Ø 60mm  
Length: 225mm



**200 FXA2CRRB-U**

Chrome

12V - 1W  
4000 °K  
Size: Base Ø 60mm  
Length: 225mm  
USB Port 5V - 2A



**200 FXB1UCR**

Chrome

12V - 1W  
3000 °K  
Size: Base Ø 60mm  
Length: 150mm  
USB Port 5V - 2.1A



**200 FXA1CRC-UX**

Chrome

12V - 1W  
3000 °K  
Size: Base Ø 50mm  
Length: 150mm  
USB Port 5V - 2.1A



**200 FXE01NDU1**

Black / Chrome

12V - 90Lm  
4000 °K  
Size: Base Ø 55mm  
Length: 150mm  
USB Port 5V - 2A



Wall Lamp

**200 FXC1N-U**

Black

12V - 2W  
3000 °K  
Size: Ø 80 x 25mm  
Length: 350mm  
USB Port 5V - 2.1A

## Flexible Reading Lights

Mechanical Switch

—USB



### 200 FXSB1.5

White

12V - 1.5W  
3400 °K  
Size: Base Ø 50mm  
Length: 200mm

USB Port 5V - 2.1A

### 200 FXSN1.5U4

Black



—USB



### 200 FXS01NU

Black

12V - 1.5W  
3400 °K  
Size: Base Ø 50mm  
Length: 350mm

USB Port 5V - 2.1A

## Flexible Reading Lights

Touch Switch



### 200 FX9CRT

Chrome

12V - 1.5W  
3000 °K  
Length: 400mm



### 200 FXA2CRBT

Chrome

12V - 1W  
4000 °K  
Size: Base Ø 60mm  
Length: 225mm

—USB



Wall Lamp

### 200 FXF1N-C

Black

12V - 2W  
3000 °K  
Size: Ø 60 x 20mm  
Length: 450mm

USB Port 5V - 2.1A

### 200 FXF1N-U

Black

3200 °K

## Ultra-slim Spot Lights

Recessed



This spot-light features an ultra-slim body in die-cast aluminum of 8 mm. The 2,70 Watt LEDs provide 150 Lumen of soft and diffused light.

Choose between four different ring colors: Chrome, silver, black or white. Rings are held in place magnetically and can easily be switched over.

### **200 SPK01CR**

Chrome

12V - 3W  
150 Lm - 3000 °K  
Size: Ø 64mm

### **200 SPK01N**

Black

## Spot Lights

Recessed



### **200 S0101WAL**

Aluminum

12V - 1.5W  
105 Lm - 3000 °K  
Size: Ø 68mm



### **200 S0101WCR**

Chrome



### **200 S0101WNE**

Black



### **200 S0101WNS**

Nickle Brushed



### **200 MSJ0.6CR**

Chrome

12V - 1W  
3000 °K  
Size: Ø 45mm

### **200 MSJ0.6CRD**

Chrome

4000 °K

### **200 MSJ0.6NS2**

Nickle Brushed

3000 °K

## Spot Lights

Recessed - Manual Switch

---



### **200 SMB1.2-18CR**

Chrome

12V - 1.56W  
3000 °K  
Size: Ø 68mm

### **200 SMB1.2-18NS**

Nickle Brushed

### **200 SMB18AL2**

Brushed Aluminum

---



### **200 SCB3N2**

Black

12V - 3W  
3000 °K  
Size: Ø 68mm

### **200 SCB3ND1**

Black

4000 °K

---



### **200 SQ1.6-24CR**

Chrome

12V - 1.46W  
3000 °K  
Size: 65 x 65mm

### **200 SQ1.6-24AL**

Brushed Aluminum

4000 °K

---



### **200 MSJ1.5CR**

Chrome

12V - 1.40W  
3000 °K  
Size: Ø 45mm

### **200 SQ1.6-24AL**

Black

---



### **200 MSJ1CRD**

Chrome

12V - 1W  
4000 °K  
Size: Ø 45mm

## Spot Lights

Recessed - Touch Switch



### 200 SMB1.2CRT

Chrome  
12V - 1.5W  
3000 °K  
Size: Ø 68mm

### 200 SMB1.2NST1

Nickle Brushed



### 200 SQ1.6-24CRT

Chrome  
12V - 1.69W  
3000 °K  
Size: Ø 68mm

### 200 SQ1.6-24ALT

Brushed Aluminum  
4000 °K



### 200 SCB3CRT2

Chrome  
12V - 2.70W  
3000 °K  
Size: Ø 68mm



### 200 S0201WAL2

Aluminum  
12V - 1.50W  
3000 °K  
Size: Ø 68mm



### 200 SMB1.2NSTM

Nickle Brushed  
12V - 1.56W  
3000 °K  
Size: Ø 68mm

## Swivel Spot Lights

Recessed - Touch Switch



### 200 S0202WCR

Chrome  
12V - 1.50W  
3000 °K - 115  
Size: Ø 68mm

### 200 S0202WNE8

Black

### 200 S0202WNS

Nickle Brushed

## Swivel Spot Lights

Recessed - Manual Switch



### 200 S0102WAL

Aluminum

12V - 1.5W  
115 Lm - 3000 °K  
Size: Ø 68mm



### 200 S0102WCR

Chrome



### 200 S0102WNE

Black



### 200 S0102WNS

Nickle Brushed



### 200 ELO1-18NS

Nickle Brushed

12V - 1.57W  
3000 °K - 114Lm  
Size: Ø 68mm



### 200 ELO1CR

Chrome

12V - 2.66W  
3000 °K - 55Lm  
Size: Ø 70mm



### Adjustable spotlight + connectors

### 200 S0102WAL2

Aluminum

12V - 1.29W  
3000 °K - 115Lm  
Size: Ø 68mm



### 200 MSR1N

Black

12V - 1.47W  
3000 °K - 38Lm  
Size: Ø 35mm



### 200 MSO1N

Black

12V - 0.75W  
3000 °K - 22Lm  
Size: Ø 35mm



### 200 MSRO1N

Black

12V - 0.75W  
3000 °K  
Size: Ø 35 x 20mm



### 200 MSSO1N

Black

12V - 0.75W  
3000 °K - 22Lm  
Size: Ø 35 x 20mm

Spot Lights  
Recessed - IP-Graded



**200 CA0.4CRIP**

Chrome  
12V - 0.38W  
3000 °K - 22Lm  
Size: Ø 30mm

**200 CA0.4CRIPD**

Chrome  
3600 °K



**200 SMB1-18NSIP**

Nickle Brushed  
12V - 1.66W  
3000 °K - 119Lm  
Size: Ø 68mm

**200 SMB18ALIP2**

Brushed Aluminum



**200 SMB18CRIP6**

Chrome  
12V - 1.68W  
3000 °K - 119Lm  
Size: Ø 68mm

**200 SMB18NSIP6**

Nickle Brushed



**200 CA0.3CRIP**

Chrome  
12V - 0.20W  
6000 °K - 15Lm  
Size: Ø 30mm



**200 CA0.4NIPD**

Black  
12V - 0.41W  
4000 °K - 22Lm  
Size: Ø 30mm



**200 S0103WNE**

Black  
12V - 1.50W  
3000 °K - 115Lm  
Size: Ø 68mm

## Spot Lights

Surface Mounted - Manual Switch



### 200 MC3RDAL1

Brushed Aluminum

12V - 4W  
3000 °K  
Size: Ø 100 x 7mm

### 200 MC3RDSX

Silver



### 200 MRC15CR1

Chrome

12V - 1.69W  
3000 °K - 123Lm  
Size: Ø 80 x 8mm

### 200 MRC15CRD

Chrome

4000 °K



### 200 RV6SDI

Silver

12V - 2W  
4000 °K  
Size: 84 x 26mm

Swivel and Tilt

## Spot Lights

Surface Mounted - Touch Switch



### 200 SMS1-24CRDT

Chrome

12V - 1.71W  
4000 °K - 118Lm  
Size: Ø 90 x 24mm

### 200 SMS1-24ST

Silver

3000 °K

Swivel and Tilt



### 200 SMBA1.2NST

Nickle Brushed

12V - 1.55W  
3000 °K - 110Lm  
Size: Ø 68 x 15mm

## Mini Spot Lights Step Lights



### 200 RLS0.06BCR

Chrome - Blue  
12V - 0.21W  
1.4Lm  
Size: Ø 18mm

### 200 RLS0.06PCR

Chrome  
3000 °K

### 200 RLS0.06PCR1

Chrome  
4500 °K



### 200 RLS0.06PN

Black  
12V - 0.21W  
3000 °K - 5.8Lm  
Size: Ø 18mm

## Track Lights



### Spot slider for Track System

### 200 TRS-N

Black  
12V - 0.60W  
3000 °K - 61Lm  
Size: 49 x 19 x 36mm

### 200 TRS-S

Silver



### Spot slider for Track System

### 200 TRSI-N

Black  
12V - 0.60W  
3000 °K - 61Lm  
Size: 51 x 19 x 36mm

### 200 TRSI-S

Silver

— USB



### USB socket for Track System

### 200 TR-USB-N

Black  
12V  
Size: 46 x 17 x 39mm  
5V - 2A USB

### 200 TR-USB-S

Silver

## Cabinet Lights



### 200 WRS1S

Silver

12V - 1.80W  
2700 °K - 140Lm  
Size: 132 x 65 x 12mm



### 200 WRS4S

Silver

12V - 0.50W  
6000 °K - 34Lm  
Size: 30 x 30 x 18mm



### 200 DS65-P

Silver

3 x AAA - 0.80W  
4000 °K  
Size: 70 X 45 X 22mm

Battery Operated



### 200 WRS138SM

Sliver

3 x AAA - 0.72W  
3000 °K - 50Lm  
Size: 135 x 75 x 25mm

Battery Operated



### 200 DS67-P

Rechargeable battery  
cabinet light with  
USB-C cable

White

3000 °K  
Size: 68 x 28 x 9mm

## LED Bars

Recessed



### 200 LB360S

12 x 24 x 360mm

4.40W - 307Lm

12V - 3000 °K

### 200 LB650S


12 x 24 x 650mm

6.90W - 490Lm

12V - 3000 °K

## LED Bars

Recessed - Touch Switch



### 200 LB650ST

12 x 24 x 650mm

6.90W - 490Lm

12V - 3000 °K

### 200 LB950ST

12 x 24 x 950mm

11.60W - 904Lm

12V - 3000 °K




<b>200 LB930NT</b>	21 x 7 x 930mm		12V - 3000 °K
<b>200 LB700NT</b>	21 x 7 x 700mm	6.80W - 404Lm	12V - 3000 °K
<b>200 LB1000NT</b>	21 x 7 x 1000mm	10.30W - 590Lm	12V - 3000 °K
<b>200 LB762NDT</b>	21 x 7 x 762mm		12V - 4000 °K
<b>200 LB1000NT</b>	21 x 7 x 700mm	6.70W - 493Lm	12V - 4000 °K



<b>200 LB1000DI</b> Aluminum	12 x 24 x 1000mm	12.60W - 830Lm	12V - 4000 °K
<b>200 LB660DI</b>	12 x 24 x 660mm	8.30W - 570Lm	12V - 4000 °K
<b>200 LB800DI</b>	12 x 24 x 800mm	11.60W - 904Lm	12V - 4000 °K
<b>200 LB1100DI</b>	12 x 24 x 1.100mm	13.90W - 916Lm	12V - 4000 °K
<b>200 LB1220DI</b>	12 x 24 x 1.200mm	15.00W - 1010Lm	12V - 4000 °K
<b>200 LB1280DI</b>	12 x 24 x 1.280mm	16.00W - 1060Lm	12V - 4000 °K


## LED Bars Surface Mounted



<b>200 RR1.8ASMI</b> Silver Adjustable	ø12mm, L: 350mm	1.20W - 77Lm	12V - 3500 °K
--	-----------------	--------------	---------------



<b>200 LB300S</b> Aluminum	27 x 15 x 300mm	3.00W - 260Lm	12V - 3000 °K
-------------------------------	-----------------	---------------	---------------



<b>200 LB500S</b> Aluminum	27 x 15 x 500mm	5.50W - 520Lm	12V - 3000 °K
-------------------------------	-----------------	---------------	---------------



<b>200 KLB5S</b> Silver	40 x 15 x 320mm	5.00W	12V - 4000 °K
----------------------------	-----------------	-------	---------------

## LED Bars

Surface Mounted - Touch Switch



<b>200 SLB1000TD</b>	7 x 16 x 1000mm	10.40W - 832Lm	12V - 4000 °K
<b>200 SLB600TD</b>	7 x 16 x 600mm	5.60W - 448Lm	12V - 4000 °K
<b>200 SLB800T</b>	7 x 16 x 800mm	8.00W - 640Lm	12V - 3000 °K
<b>200 SLB800TD</b>	7 x 16 x 800mm	8.00W - 640Lm	12V - 4000 °K



<b>200 RR300DT</b>	ø13mm, L: 300mm	3.50W - 350Lm	12V - 4000 °K
<b>200 RR600DT</b>	ø13mm, L: 600mm	6.50W - 620Lm	12V - 4000 °K

## LED Strips and Profiles

### MINI-CUT LED Strip

High Efficiency LED Strip 80 SMD2835 LED / m



Mini-cut LED Strips increase brightness by 30 % at 4,8 Watt/m, compared to standard 60 LED/m LED strip. Alternatively, they can reach the standard LED strip luminance with less than 25% current consumption.

With 80 LED / m the light output is more homogeneous and the 25 mm cutting distance allows a more precise trimming of the LED strip.

4.8 W / m - 143 Lumen / Watt - 685 Lumen / Meter  
3.5 W / m - 143 Lumen / Watt - 500 Lumen / Meter

### COB LED Strip



The COB LED Strip can be tuned to different outputs from 4.8 up to 9.6 Watt / m in the 320 LED / m configuration. Higher outputs are available with 480 LED / m.

4.8 W / m - 94 Lumen / Watt - 450 Lumen / Meter



### Neon Flex Strip

4 x 8 mm Neon flex, with uniform light output. Available in precut lengths according to customer's requirements.



### CSP LED Strip

This LED Strip is fitted with 320 CSP (Chip Scale Package) LEDs. The CSP LED is an integrated component that has no soldered wire connections between the chip and the support. This makes it more efficient due to reduced thermal resistance and heat transfer, and offers less possible failure points.

4.8 W / m - 107 Lumen / Watt - 513 Lumen / Meter

## Garage and Portable Lights



### Garage Lamp

#### 200 LS9BDI

White

12V - 2.50W  
4000 °K  
Size: 180 x 105 x 35mm



### Compact Lamp

#### 200 PL2.5S

Silver

12V - 2.50W  
6000 °K  
Size: 218 x 70 x 40mm



### Garage Light

#### 200 SLG-B

White

12V - 3.80W  
3000 °K  
Size: Ø 130 x 14mm



### Mini flashlight with rechargeable battery

#### 200 DT4-K

Black

4000 °K  
Size: Ø 20 x 70mm

### Rechargeable Table Lamp

This lamp can be mounted to the stand, a wall mount or to a clip. Rechargeable 1.200 mAh Li-ion battery.

Touch-Switch dimmable on three different levels. Natural white light.



#### 200 TLA001BTD

White

2W - 4000 °K



#### 200 TLA001NTD

Black

2W - 4000 °K

## Awning Lights



### 200 AW7B

White  
12V - 7.00W  
450Lm - 4000 °K  
Size: 401 x 50 x 35mm

### 200 AW7N

Black



### 200 AW7S

Silver



### 200 AWX5B

White  
12V - 5.00W  
270Lm - 4000 °K  
Size: 364 x 35 x 50mm

### 200 AWX5N

Black

### 200 AWX5S

Silver

COB Lights



### 200 AWX5B-PIR

White  
12V - 5.00W  
270Lm - 4000 °K  
Size: 364 x 35 x 50mm

COB with  
PIR Sensor



### 200 AWX8B

White  
12V - 8.00W  
370Lm - 4000 °K  
Size: 647 x 45 x 70mm

### 200 AWX8N

Black

### 200 AWX8S

Silver

COB with  
Rain Channel



### 200 AW8S-PIR

Silver  
12V - 8.00W  
430Lm - 4000 °K  
Size: 647 x 45 x 70mm

PIR Sensor &  
Rain Channel



### 200 AW6B

White  
12V - 5W  
440Lm - 4000 °K  
Size: 310 x 45 x 53mm

## External Over-door Lights



### 200 ODL750B

White

12V - 9.50W

4200 °K

Size: 34 x 42 x 750mm



### 200 ODL750S

Silver / Aluminum

## Awning Light Track

### Awning Light Profile

This light profile has been developed to be installed under awnings. It provides «Soft-TONE» light and can be custom-fitted to most wall-mounted awnings with a length of up to 19.7 ft.

The system consists of a series of triangular-shaped aluminum profiles and a waterproof LED profile which is glued onto the aluminum profile.



### 200 NFAP1M

Triangular shaped aluminum profile

12V - 9.6W

4000 °K

Length: 3.25 ft

### 200 NFA4.5D

IP65 light profile

Length: 14.75 ft

### 200 NFA6D

IP65 light profile

Length: 19.7 ft

## Custom-Designed Lighting

### 200 VAN-PRO

This light is an example of a custom solution designed for a specific application. It installs on the side door frame of ProMaster vans and features a comfortable continuous Soft-TONE light. The integrated rain gutter function keeps water from dripping inside the vehicle when the door is open. Installing the light is easy and only requires three screws.

### Compatible with the following vehicles:

- Fiat Ducato X244
- X250/X290 and Citroën Jumper / Peugeot Boxer starting from MY 2006



### 200 VAN-PRO-LH

For RDH Vehicles  
(Left Sliding Door)

12V - 8.5W

180 LED/m SMD 2835

4000 °K - 425Lm

Milky Diffuser

Length: 4.9 ft

### 200 VAN-PRO-RH

For LDH Vehicles  
(Right Sliding Door)



Dimatec has been specializing in producing low voltage and low energy consumption lighting devices since 1990. It strives to develop solutions that best fulfill the specific needs of the RV industry and it's end users.

Both function and form are considered in order to develop products that seamlessly integrate into your vehicle's interior design. The creative part of development for lighting fixtures is a big focus area. Dimatec collaborates with major OEMs every year to create new products— customized for the RV industry. Each new solutions is guaranteed to be advanced energy saving and low voltage lighting.

**Discover Dimatec Lighting online at:  
[www.Elwellcorp.com/dimatec](http://www.Elwellcorp.com/dimatec)**

